



FUEL ADDITIVES

# BIOBORDC<sup>®</sup>

## Diesel Fuel Conditioner

### *Summer Blend*

**BioborDC<sup>®</sup> *Summer Blend*** is a multifunctional warm-weather diesel fuel conditioner to enhance the stability and operability of ultra-low sulfur diesel fuels. Components of **BioborDC<sup>®</sup>** will provide exceptional fuel stability, added lubricity, detergency and water control. With continued use, **BioborDC<sup>®</sup>** enhances the performance and life of diesel fuels while protecting and cleaning vital engine components, maintaining fuel economy and reducing emissions.

## What does BioborDC *Summer Blend* do for you?

- ✔ **Fuel Stability**      **Contains an ashless thermal stability additive formulated to prevent the degradation of mid-distillate fuels.**
  - Prevents problems associated with gum and residue
  - Reduces diesel degradation and sludge formation
  - Allows longer storage periods and decreases filter/injector plugging
  
- ✔ **Lubricity**      **Adds vital fuel lubricity increasing the lubrication properties of ULSD.**
  - Protects fuel injectors and fuel pumps
  - Extends the life and prevents pre-mature wear of close tolerance components.
  - Provides additional corrosion protection
  
- ✔ **Detergent**      **A multifunctional, ashless additive package to improve fuel quality and engine operation by cleaning injectors and particulates.**
  - Meets Cummins L-10 performance requirements for detergency
  - Keeps injectors clean—prevents injector sticking and plugging
  - Improves fuel economy
  - Reduces emissions and smoke
  - Reduces power loss
  - Prevents fuel filter plugging from deposits
  - Reduces deposits throughout fuel system
  - Achieves Peugeot DW-10 Injector Coking Test—Keep Clean rating
  - Additional corrosion and stability protection
  
- ✔ **Controls Water and Corrosion**      **Prevents water-related issues and corrosion.**
  - Disperses moisture and prevents water accumulation
  - Helps prevent microbe growth—algae and bacteria infestation.

| Treat Rate...   |
|---|
| Use at a ratio of<br><b>1 gallon to every 3,000 gallons</b><br>of diesel fuel |
| *Ultra-Low Sulfur Diesel compliant<br>Contains less than 15ppm sulfur         |

| Other Hammonds Products... |  |
|----------------------------|--|
|                            | <p><b>Diesel biocide and lubricity additive</b><br/>The Worldwide Standard Since 1965</p> <p><b>Concentrated diesel antigel, de-icer and lubricity additive, for cold-temperature operation</b></p> <p><i>Winter Blend</i> for cold-weather operation<br/>cold-flow improvers replace moisture dispersants</p> |

