

Diesel Fuel Anti-Gel with Lubricity

Biobor ColdFlo[®] with **Lubribor**[®] is a concentrated diesel fuel additive formulated to provide superior cold weather operability and engine protection. **ColdFlo**[®] with **Lubribor**[®] reduces the **pour point** and **cold filter plug point** of diesel fuel while also **preventing ice** and **lubricating injectors and pumps**. The use of this additive will enable diesel fuel to flow through filters at much lower temperatures and prevent fuel icing while also adding vital lubricity to ULSD.

Applications: ColdFlo® with **Lubribor®** is specially-formulated for use in low-sulfur diesel fuels and heating oils, and is commonly used in trucks, farm equipment, locomotives, diesel boats, industrial and construction equipment.

What does Biobor ColdFlo® with LubriBor® do for you?

- ✓ Inhibits wax crystal growth
- Reduces Pour Point of diesel fuel
- **Reduces Cold Filter Plug Point** by up to 30° F
- Jet fuel de-icer prevents ice blockages and fuel filter icing
- Adds lubricity to protect injectors and fuel pumps
- Minimizes the need for kerosene dilution
- ULSD compliant-contains less than 15 ppm sulfur

Available sizes	Treats
32oz	
1 gal	1,500-3,000 gal
2.5 gal	3,750 -7,500 gal
5 gal	7,500-15,000 gal
55 gal	82,500-165,000 gal
330 gal.Tote	. 495,000-990,000 gal

Treat Rates	CFPP Reduction*
1:3,000	10-15°F
1:1,500	20-30°F (26° AVG)
1:1,000	30°F
Diesel fuel should be at least 10°F above cloud point when treated.	

Store above 32°F. Additive pour point is -16.6°F.

FUEL ADDITIVES

*Additive performance may vary depending on the quality of fuel treated.





6951 West Little York • Houston, Texas 77040 • (800) 548-9166