

# BIOBOR® DC Plus CETANE

## SUMMER BLEND DIESEL CONDITIONER

**Biobor®DC+Cetane** is a multifunctional **warm-weather diesel fuel conditioner** to enhance the stability and operability of ultra-low sulfur diesel fuels. Components of **Biobor®DC+Cetane** will provide increased cetane, exceptional fuel stability, added lubricity, detergency and water control. With continued use, **Biobor®DC+Cetane** enhances the performance and life of diesel fuels while protecting and cleaning vital engine components, maintaining fuel economy and reducing emissions.

- + Cetane**                      **Raises cetane levels to improve the ignition quality of the fuel**
  - Improves fuel economy and cold starting
  - Reduces exhaust emissions and smoking, especially NO<sub>x</sub>
- + Fuel Stability**            **Contains an ashless thermal stability additive formulated to prevent the degradation of mid-distillate fuels.**
  - Prevents problems associated with asphaltenes and sludge formation
  - Decreases fuel filter plugging and extends storage periods
- + Lubricity**                    **Adds vital fuel lubricity increasing the lubrication properties of ULSD**
  - Protects fuel injectors and fuel pumps
  - Extends the life and prevents pre-mature wear of close tolerance components
- + Detergent**                    **A multifunctional additive package to improve fuel quality and engine operation by cleaning injectors and particulates.**
  - Keeps injectors clean—prevents injector sticking and plugging
  - Improves fuel economy and restores power
  - Reduces emissions and smoke
  - Reduces power loss
  - Prevents HPCR Injection issues—IDID and asphaltenes
  - Meets Cummins L-10 performance requirements for detergency
  - Achieves Peugeot DW-10 Injector Coking Test—Keep Clean rating
- + Controls Water and Corrosion**    **Prevents water-related issues and corrosion.**
  - Disperses moisture and prevents water accumulation
  - Helps prevent microbe growth—bacteria and fungi infestation
  - Prevents corrosion on metal components

TREAT RATE
Use at a ratio of <b>1 gallon to every 2,000 gallons</b> of diesel fuel
Ultra-low sulfur diesel compliant. Contains less than 15ppm sulfur.

Distributed by...

**OTHER HAMMONDS PRODUCTS**

 Diesel biocide and lubricity additive	 Concentrated diesel antigel, de-icer	 WINTER BLEND for cold-weather operation.
--	---	--



6951 West Little York • Houston, Texas 77040 • (800) 548-9166 [www.biobor.com](http://www.biobor.com)